



Racing



SKF Racing Wheel Bearings

SKF Designation *sealed bearings	d (mm)	D (mm)	B (mm)	C (N)	Co (N)	Single or Double row
BAH-0144*	49	88	46	65000	62000	D
633007 C*	50	90	34	60500	47500	D
BAH-0197*	50	90	34	60500	47500	D
S7011 ACDGA/P4AVP304*	55	90	18	37100	31000	S
S71912 ACDGA/P4AVP3042*	60	85	13	18600	14600	S
71913 ACDGA/P4A	65	90	13	19500	16000	S
71914 ACDGA/P4A	70	100	16	32500	32500	S
71915 ACDGA/P4A	75	105	16	33800	35500	S
S71917 ACDGA/P4AVP304*	85	120	18	43600	45500	S
S71918 ACDGA/P4AVP3042*	90	125	18	44200	48000	S
BAH-0183*	90	115	13	22100	26500	S
S71919 ACDGA/P4AVP304*	95	130	18	46200	52000	S
BAH-0163A*	100	127	13	28100	34500	S
BAH-0180	105	130	13	24200	31500	S
BAH-0192	101.6	134.938	15.875	41000	48000	S
BAR-5049C*	Corvette C5/C6 HUB			56000	61500	D
BAR-0265/BAR-0265A*	Single Nut HUB Unit			54000	51000	D
BAR-0266/BAR-0266A*	Xtracker Single Nut HUB Unit			46200	33500	D
				41000	29000	

Bearings can be supplied with ceramic balls on request.

